



Produced by the United States Geological Survey Topography compiled 1936. Planimetry derived from imagery taken 1994 and other sources. Public Land Survey System and survey control current as of 1987. North American Datum of 1983 (NAD 83). Projection and 2 500-meter ticks: Universal Transverse Mercator, zone 17 North American Datum of 1927 (NAD 27) is shown by dashed corner ticks. The values of the shift between NAD 83 and NAD 27 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software. There may be private inholdings within the boundaries of the National or State reservations shown on this map. Dotted land lines established by Dade County. Landmark buildings verified 1987.



CONTOUR INTERVAL 5 FEET NATIONAL GEODETIC VERTICAL DATUM OF 1929 TO CONVERT FROM FEET TO METERS, MULTIPLY BY 0.3048

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25286, DENVER, COLORADO 80225 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION table with symbols for Primary highway, Secondary highway, Interstate Route, U.S. Route, State Route, Light-duty road, and Unimproved road.

Legend table with numbers 1-8 corresponding to map symbols for Cooperstown, South Miami NW, South Miami, Gosman Hammock, Perrine, Royal Palm Ranger Station, Homestead, and Arsenals Keys.

GOULDS, FL 1994

NIMA 4935 III S-SERIES V847

