



ELEVATIONS IN METERS

Scale 1:50,000
0 1000 2000 3000 4000 Meters
0 1 2 3 Statute Miles
0 1000 2000 3000 4000 Yards
0 1 2 Nautical Miles

CONTOUR INTERVAL 20 METERS WITH SUPPLEMENTARY CONTOURS AT 10 AND 5 METER INTERVALS
ΕΚΦΑΝΤΙΣΗ 20 ΜΕΤΡΑ ΜΕΤΑ ΒΟΗΘΗΤΙΚΩΝ ΚΑΜΥΓΩΝ 10 ΜΕΤΡΑ ΚΑΙ 5 ΜΕΤΡΩΝ

GLOSSARY-ΑΕΙΩΘΙΟΝ

Ada	island	Νήσος
Bata	swamp	Ελάς, Τόπος
Brdo	hill	Αόλις
Breg	valley	Αόλις
Dolina	valley	Κοιλιά
Ergola	stud farm	Εργοστάσιο
Grada	sand bank	Αμμοθώπιον
Humka	mound	Στοιβά
Kazneni zavod	prison	Γεφυλάκι
Manastir	monastery	Μοναστήριον
Posta	post office	Ταχυδρόμιο
Stacija	station	Σταθμός

INDEX TO ADJOINING SHEETS

3284 I	3284 IV	3284 II
3284 II	3284 III	3284 I
3284 I	3284 IV	3284 I

BOUNDARIES

Boundary representation is not necessarily authoritative. Names and boundaries of administrative divisions in Serbia and Montenegro have asserted the formation of a joint independent state, but this entity has not been formally recognized as a state by the United States.

Prepared by the Army Map Service (S&H), Corps of Engineers, U.S. Army, Washington, D.C. Compiled in 1959 from Karte des Nordwest-balkan, 1:50,000, Generalstab des Heeres, Sheets 66/3, 66/4, edition 1943. Planimetric detail revised by photo-planimetric methods. Map not field checked.

LIMITED REVISIONS AS OF 1995 MAP INFORMATION AS OF 1992
Prepared and published by the Defense Mapping Agency, St. Louis, Missouri.

LEGEND ΥΠΟΜΝΗΜΑ
On this map a lane is generally considered as being 8 to 12 feet (2.5 to 3.6 meters) in width. Known exceptions are indicated on the face of the map.
Αυτήν την κλίμακα (σχήμα) οριοθέτηση γενικά είναι 8-12 μέτρα (2,5-3,6 μ.) πλάτος (εξαιρέσεις αναφέρονται επί της όψης του χάρτη).

ROADS ΟΔΟΙ:
All weather, hard surface, two or more lanes wide
Αυτήν την κλίμακα (σχήμα) οριοθέτηση γενικά είναι 8-12 μέτρα (2,5-3,6 μ.) πλάτος (εξαιρέσεις αναφέρονται επί της όψης του χάρτη).

RAILROADS ΣΙΔΗΡΟ ΟΔΟΙ (ΡΕΛΙΑ):
Normal gauge 1.44 m (4' 8 1/2")
Κανονικό μέγεθος 1,44 μ. (4' 8 1/2")

BOUNDARIES ΟΡΙΑ:
International (Εθνικά)
Primary administrative (Κεντρικά)
Secondary administrative (Πρωτοβάθμια)
Tribal (Εθνογενή)
Prominent fence (Εξέχοντα φράγματα)
Earth dam (Λέβητος)

Spot elevations in meters: Checked/unchecked
Υψόμετρος επί μέτρων: Ελεγχθέντα/μη ελεγχθέντα

CAUTION

THIS PRODUCT MAY NOT CONFORM TO THE HORIZONTAL ACCURACY REQUIREMENTS FOR 1:50,000 TOPOGRAPHIC LINE MAPS. EXTREME CAUTION SHOULD BE USED WHEN MAKING MEASUREMENTS.

REVISIONS IN PURPLE

LEGEND

Disturbance taller than 61m

Building area
Building
All weather hard surface road
All weather loose surface road
Fair or dry weather, loose surface
Asphalt or concrete
Footpath, trail
Tree lined road
Railroad
Single track
Double track
Narrow gauge
Boundary
Primary administrative
Secondary administrative
Tribal
Prominent fence
Earth dam
Spot elevations in meters

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

COORDINATE CONVERSION WGS 84 TO ED 50

Geographic: Add 2.7' Long, Add 3.1' Lat.

GRID ZONE DESIGNATION

34T
50Q

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO METERS OR FEET:
Geographic: Add 2.7' Long, Add 3.1' Lat.