

V778
EDITION 2-NIMA




Prepared and published by the National Imagery and Mapping Agency.

LEGEND

Tint indicates built-up areas in which only landmark buildings are shown
ROAD DATA 1963-64
In developed areas, only through roads are classified

Hard surface, heavy duty road, four or more lanes wide	Improved light duty road, street
Hard surface, heavy duty road: Two lanes wide; Three lanes wide	Unimproved dirt road
Hard surface, medium duty road, four or more lanes wide	Trail
Hard surface, medium duty road: Two lanes wide; Three lanes wide	Route markers: Federal, State
RAILROADS	Buildings
National Standard gauge	Bench mark, monumented
Narrow gauge	Bench mark, non-monumented
In street	Spot elevations in meters: Checked: Unchecked
Carline	Light, lighthouse, Windmill, wind pump; Water mill
BOUNDARIES	Woods or brushwood
National	Vineyard, Orchard
State (with monument)	Intermittent lake
County	Intermittent stream; Dam
Township	Marsh or swamp
Corporate limits	Rapids; Falls
Military reservation	Large rapids; Large falls
Other reservation	
Land subject to inundation	



ELEVATIONS IN METERS
CONTOUR INTERVAL 10 METERS
VERTICAL DATUM: SEA LEVEL DATUM OF 1929

TRANSVERSE MERCATOR PROJECTION
HORIZONTAL DATUM: 1927 NORTH AMERICAN DATUM

BLACK NUMBERED LINES INDICATE THE 1:50,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 14

USERS SHOULD REFER CORRECTIONS, ADDITIONS, AND COMMENTS TO THE NIMA OPERATIONAL HELP DESK: 1-800-45-0896, COMMERCIAL 314-263-4864, DSN 689-4864; OR WRITE TO: DIRECTOR, NATIONAL IMAGERY AND MAPPING AGENCY, ATTN: IS, MAIL STOP 4-8, 4805 SAIGANOORE ROAD, BETHESDA, MD 20818-5002

GRID ZONE DESIGNATION: 14S	TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS
100,000 M. SQUARE IDENTIFICATION	SAMPLE POINT A: INDUSTRY
	<ol style="list-style-type: none"> Read letters identifying 100,000 meter square in which the point lies. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself. Estimate tenths from grid line to point. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself. Estimate tenths from grid line to point.
<p>IGNORE THE SMALLER figures of any grid number: these are for reading the full coordinates. Use ONLY the LARGER figures of the grid number: example: 431000</p>	<p>SAMPLE REFERENCE: PUS050A5</p> <p>If reporting beyond 10° in any direction, prefix Grid Zone Designation as: 14SP09050A5</p>

Reprinted by NIMA 08-92 PRINTED BY DMATC, 3-80

BOUNDARIES ADJOINING SHEETS

1	2	3	6562 IV	6562 I	6562 V
4	5	6	6562 III	6562 II	6562 III
7	8	9	6562 IV	6561 I	6561 V
10	11	12			

Sheet 6562 II falls within N 14 S, 9502, 1200,000

1960 G-M ANGLE 8° (140 MILS)

GRID CONVERGENCE 119° (21 MILS) FOR CENTER OF SHEET

TO CONVERT A MAGNETIC AZIMUTH TO A GRID AZIMUTH TO A MAGNETIC AZIMUTH ADD G-M ANGLE

TO CONVERT A GRID AZIMUTH TO A MAGNETIC AZIMUTH SUBTRACT G-M ANGLE

FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225 OR RESTON, VIRGINIA 22092

METRIC CONVERSION OF CONTOURS AND ELEVATIONS 1978

THIS MAP IS RED LIGHT READABLE

WAKEFIELD, KANSAS

NSN 7643014044024
NIMA Ref No V778X65622

ED NO 002