



LEGEND / SIGNOS CONVENCIONALES. Table listing symbols for populated places, roads, railroads, boundaries, and various features with their corresponding map symbols.

NOTES. LANE ON THIS MAP IS CONSIDERED TO BE FROM 2.5 METERS (8 FEET) TO LESS THAN 5.5 METERS (18 FEET) WIDE. UN ESTE MAPA SE CONSIDERA QUE UNA VIA TIENGA UN ANCHO MÍNIMO DE 2.5 METROS (8 PIES) HASTA UN ANCHO MÁXIMO DE MENOS DE 5.5 METROS (18 PIES).

THIS MAP IS RED-LIGHT AND BLUE/GREEN LIGHT READABLE. ESTE MAPA ES LEGIBLE POR LUZ ROJA Y LUZ AZUL/VERDE.

ELEVATIONS IN METERS. CONTOUR INTERVAL 20 METERS. ELEVACIONES EN METROS. INTERVALO DE CURVAS 20 METROS.

100 METER REFERENCE. WHEN REPORTING ACROSS A 100-METER LINE, PREFIX THE 100-METER SQUARE IDENTIFICATION IN WHICH THE POINT LIES.

GRID CONVERSIONS. TO CONVERT FROM GRID TO MAGNETIC AZIMUTH, ADD G-M ANGLE.

LIMITED DISTRIBUTION. Distribution authorized to DOD, LAW ENFORCEMENT, AND OTHER AGENCIES.

