



Table with 4 columns: IPL Sample No., Elevation, Azimuth, and Date. It lists the specific parameters for each of the 121 mosaic tiles.

DESCRIPTION OF SCENE

This view north of the lander shows the level rock-strewn plains of Utopia Planitia. Some of the large blocks appear to lie on the fine-grained material that partly covers the interblock areas. This appearance probably is due to scour or erosion by the martian winds that have carried away the fine-grained material from between the larger rocks. Some of the boulders seem to stand on pedestals of the protected material (line 320, sample 1130). Most of the rocks are highly pitted or vesicular. The vesicles probably formed from gas bubbles in a cooling lava. A few of the rocks are fine-grained and appear to be loessic, probably by wind erosion (line 430, sample 2320). A shallow trough crosses the main field, trending approximately east-west (line 330, sample 300; line 470, sample 2250). The trough is 8 m from the lander, about 1 m wide, and 10 cm deep. Small drifts occupy the floor of the trough (line 460, sample 1050). The trough is part of a polygonal network which suggests that it may have formed from cracks owing to contraction during cooling of a basaltic lava flow or to thermal expansion and contraction of frozen ground.

The meteorological instruments used to measure the temperature, pressure, speed, and direction of the martian winds are mounted on the end of the white tubular arm (line 20, sample 290) at the right of the scene. The prominent object at the lower right is the surface sampler (line 800, sample 1750). The true form of the instrument is not apparent in the mosaic; three pictures were taken when the instrument was in different positions so that a minimum of the surface would be occulted.

THE VIKING MISSION

Two Viking spacecraft, each consisting of an orbiter and lander, were launched from Kennedy Space Center on August 20 and September 9, 1975. The Viking 1 spacecraft arrived at Mars on June 19, 1976, and was placed in a highly elliptic orbit around the planet at a pericapsis altitude of nearly 1500 km. The orbiter cameras were used in conjunction with other instrumental methods to find a suitable landing site for the lander. After about 30 days in orbit, the lander was separated from the orbiter, and on July 20, 1976, Viking Lander 1 touched down on the surface of Mars at 31° 22' 48" N, and 108° 47' 06" W (Vicki and Jones, 1980) on the west edge of a large basin called Chryse Planitia. It landed in a stable position at a 3° tilt downward in the direction 284.9° clockwise from north.

The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footprint 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the cameras responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (47° 06' N, 225° 13' W), more than 6500 km northeast of Lander 1 (Mars and others, 1977; Davies and others, 1978). Lander 2 faces approximately north and sits 8.2° downward in the direction of 277.4° clockwise from north. The viewing direction of its cameras when pointed in a direction normal to the front of the lander is 29.0° clockwise from north along the horizon. The cameras on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction.

During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 482 pictures from Viking Lander 2 data. The extended mission of Viking began December 15, after solar conjunction, and ended in June 1978. During this period, an additional 1636 pictures were obtained from Lander 1 data and 1211 pictures from Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the *Journal of Geophysical Research*, v. 82, no. 28, Sept. 30, 1977; see References.

*Latitudes are areographic (see de Vasconcelos and others, 1973).

VIKING LANDER MOSAICS

The Viking Lander cameras acquired many high-resolution pictures of the Chryse Planitia and Utopia Planitia landing sites. Each picture is the product of computer processing on Earth of digital-image data transmitted from Mars as a result of "camera events" carried out by one of the lander camera systems. Further computer processing of data from a selected number of these events yielded a total of 10 mosaics. Two pairs of mosaics from Lander 1 data (one mosaic from each camera) consisted of one pair made with data acquired in the morning (0700-0800 hours) and one pair made with data acquired in the mid-afternoon (1400-1530 hours). Similarly, three pairs of mosaics for the Lander 2 site consisted of one pair between 0700 and 0800 hours, one pair at noon, and one pair between 1700 and 1800 hours.

Procedures used for processing the Viking Lander camera data were described by Levinthal and others (1977). The individual camera events used in each mosaic are identified in the outline of the accompanying camera view. Detailed descriptions and reproductions of these camera events were given by Tucker (1978). Copies of the Viking Lander pictures can be obtained from the National Space Science Data Center, Goddard Space Flight Center, Greenbelt, MD, 20771.

The Lander camera system (Hack and others, 1975a) has selectable focus settings for a depth of field from 1.2 m to infinity in the high-resolution (0.04° instantaneous field of view) mode. The survey (low-resolution) mode has an instantaneous field of view of 0.12°; this mode was used in the mosaic only where no high-resolution data were acquired. Each complete mosaic extends 342.5° in azimuth, from approximately 5° above the horizon to 60° below. A complete mosaic incorporates approximately 15 million picture elements (pixels). In order to manage the processing of such large data bases, each mosaic was compiled from four individual azimuthal sectors.

Most of the data used in the mosaics were selected from the primary mission. In some cases, extended-mission data were included where primary-mission coverage was absent or where the surface was obscured by the sample arm. Further selection was made on the basis of optimum focus.

The image data were photometrically corrected (Hack and others, 1975b; Patterson and others, 1977; Wolfe and others, 1978) for differences caused by variations in exposure and for solar-lighting differences caused by minor time-of-day variations in the position of the sun. The geometry was then transferred to a local Mars horizon and corrected for geometric camera errors (Patterson and others, 1977; Wolfe, 1981). The corrected pixels comprise a sector were then combined by the computer into a mosaic with optimum contrast correction was applied.

The mosaic is a composite of the best pixels of all the Lander pictures used for each sector. In the computer mosaic-making process, the image data derived from the camera events for each sector were assigned priorities on the basis of quality or detail. These data were examined by the computer in sequence according to the priorities, and the best pixels of each data set were used for the mosaic.

The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levinthal of the Department of Geodesy, Stanford University, who represented the Viking Lander Imaging Team. A detailed description of the multiple steps involved in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levinthal (1980).

GEOMETRY OF THE MOSAICS

The cameras on the Viking Lander acquire data by sampling in equal increments of elevation and azimuth angle. In the accompanying mosaic, 8 mm subtends a 1° horizontal or vertical angle, regardless of the place of measurement within the panorama. If the martian surface were flat, one pixel (0.04°) on the surface would be 1 mm wide at 40° camera elevation and 2 m wide at the horizon 3 km away. Characteristically for this type of imaging system, most straight lines in the scene appear curved in the reconstruction. This representation of the picture data differs from that of a conventional camera having "point perspective" picture geometry, in which rays are projected from object space, through the perspective point of the camera lens, to an image plane in the camera.

The geometry of the lander pictures is complicated by additional factors. Because both landers are tilted with respect to the horizon, on the uncorrected pictures the horizon resembles a sine curve. Computer rectification of the pictures results in a straight horizon along which vertical angles can be measured with respect to the local gravity vector, and horizontal angles can be measured from martian north. These angles are not related in any simple way to the azimuth and elevation angles given in "camera coordinates" for the uncorrected pictures.

There are other geometric distortions due to the camera: optic path distortion that affects a light ray after it passes the camera windows; and camera-system distortions, or "bold-down" errors, that are caused by the way the cameras are mounted on the lander. The geometric transformation used in creating the mosaics took into account the optic path distortion but not the "bold-down" errors. However, along the horizon, the error in azimuth angle is equal to the positional "bold-down" error for each camera to an accuracy of less than 1 pixel. The scale "azimuth angle from Mars north" has been adjusted to take into account this correction.

The residual azimuth angle errors are less than 1 pixel along the horizon and become larger with steeper elevation angles and larger lander tilts. For the worst case, Lander 2, camera 1, this error is a maximum of 5.7, 1 pixel at 40° elevation. The somewhat sinusoidal azimuth-dependent residual elevation error is a maximum of 3.1 pixels for Lander 2, camera 1, and approximately 1 pixel for the other cameras.

REFERENCES

Davies, M. E., Katsiyama, F. Y., and Roth, J. A., 1978. Contour map of Mars. February 1978. Rand Corp. R-82309-NASA-91 p.

Hack, F. O., Call, H. F., Patterson, W. R., and Taylor, G. R., 1975a. The Viking Mars Lander Camera: Space Science Instruments, v. 1, no. 2, p. 189-241.

Hack, F. O., Buzcher, E. E., Taylor, E. J., and Wall, S. D., 1975b. Radiometric performance of the Viking Mars Lander cameras. U. S. National Aeronautics and Space Administration Technical Memorandum TMX-72692.

Levinthal, E. C., and Jones, K. L., 1980. The mosaics of Mars as seen by the Viking Lander cameras. NASA Contractor Report, 330.

Levinthal, E. C., Green, William, Jones, K. L., and Tucker, Robert, 1977. Processing the Viking Lander camera data. *Journal of Geophysical Research*, v. 82, no. 28, p. 4237-4242.

Mars, A. P., Blockshear, W. T., Tolson, R. H., Michael, W. H., Jr., Kelly, G. M., Brenkle, J. P., and Komarek, T. A., 1977. Lander location, Mars physical ephemeris, and solar system parameters: Determination from Viking Lander tracking data. *Journal of Geophysical Research*, v. 82, no. 28, p. 4297-4301.

Morris, E. C., and Jones, K. L., 1980. Viking Lander on the surface of Mars. Review, v. 44, no. 1, p. 217-222.

Patterson, W. R., III, Hack, F. O., Wall, S. D., and Wolfe, M. R., 1977. Calibration and performance of the Viking Lander cameras. *Journal of Geophysical Research*, v. 82, no. 28, p. 3491-4400.

Tucker, R. B., 1978. Viking Lander imaging investigation: picture catalog of primary mission experiment data record. National Aeronautics and Space Administration Reference Publication 1091, 558 p.

de Vasconcelos, G. D., Davies, M. E., and Sturm, F. M., Jr., 1973. The Mars 9 areographic coordinate system. *Journal of Geophysical Research*, v. 78, no. 20, p. 4395-4404.

Wolfe, M. R., 1981. Viking Lander camera geometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 79-54, 1, 36 p.

Wolfe, M. R., Atwood, D. L., and Morrill, M. E., 1977. Viking Lander camera radiometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 77-62, v. 1, 90 p.

VIKING LANDER 2 RECTIFIED PHOTOMOSAIC
MORNING SCENE-CAMERA 2-SECTOR 1